



TROMMELS (Rotary screen) BLIK Series TR 800-3 et TR 1600-4



Blik





www.blik.fr

BLIK - Waste Recovery and Processing Equipment
Z.I. de Chenet
91490 MILLY-LA-FORET
E.mail: blik@blik.fr

telephone:
33 (0)1 64 98 79 79
fax:
33 (0)1 64 98 79 78

TTROMMELS (Rotary screen) BLIK Series TR 800-3 et TR 1600-4



TROMMEL (Rotative screen) BLIK TR 800-3- diameter 800 mm length 3000 mm

diameter of the rotary screen	800 mm
Total length	3000 mm
effective length of the screen	2700 mm
Interchangeable screen segments	
Diameter of screen holes	
Rotating brushes for cleaning the upper parts of the screen segments	according to the tries
Rotation speed	15 TPM - ajustable par variateur
Power motors	three phases 3 kw / 400 V / 50 Hz / 4 A
Outside dimensions (mm) without stand support width x depth x Height	4160 x 1200 x 1900 mm
Debit	Varies depending on product flow to be treated
refusal sorting falls at the end of screen	
Weight (KG)	450
"CE" certified - 1 year guarantee (*)	

TROMMEL (Rotative screen) BLIK TR 1600-4- diameter 1600 mm length 4000 mm

diameter of the rotary screen	1600 mm
Total length	4000 mm
effective length of the screen	3600 mm
Interchangeable screen segments	
Diameter of screen holes	
Rotating brushes for cleaning the upper parts of the screen segments	according to the tries
Rotation speed	15 TPM - ajustable par variateur
Power motors	three phases 3 kw / 400 V / 50 Hz / 4 A
Outside dimensions (mm) without stand support width x depth x Height	5160 x 1200 x 1900 mm
Debit	Varies depending on product flow to be treated
refusal sorting falls at the end of screen	
Weight (KG)	600
"CE" certified - 1 year guarantee (*)	